

**CURRENT TRANSFORMERS**  
**Models 0620RW & 0623RW**



**WINDOW SIZE: 2.0" & 2.06**

**INSULATION CLASS:**

0.6kV.BIL 10kV. Full wave

50-400 Hz

**APPLICATION:** With Wattmeters and Ammeters

**Fully Encapsulated.**

**Indoor/outdoor applications**

**CONTINUOUS THERMAL RATING:**




1.33 AT 30C. amb.; 1.0 AT 55 C. amb.

**Standard 5-amp secondary.**


**Others Available**

**CURRENT RANGE:**

100 TO 1500 AAC - \* 100 TO 1200 AAC



0620RW-\*\*



0623RW-\*\*

- Flexible Leads are UL 3173 125 degree C. CSA approved, #16 AWG 24" long.
- Non-Standard Length to be specified
- Additional ratios available
- Approximate weight 0.5lb.
- Made in United States of America  
*Similar to ITI models 1A & 1B*

CATALOG NUMBER	CURRENT RATIO	ACCURACY AT 60 Hz	BURDEN VA at 60 Hz
**50	50:5	+2%	1.0
**60	60:5	+1%	2.0
**75	75:5	+1%	2.0
**80	80:5	+1%	2.0
**100	100:5	+1%	2.0
**120	120:5	+1%	2.5
**125	125:5	+1%	2.5
**150	150:5	+1%	4.0
**200	200:5	+1%	4.0
**250	250:5	+1%	6.0
**300	300:5	+1%	8.0